


Introducing 0.85 mm




Supreme design for **ULTIMATE** Crossability and Deliverability

The Most Competitive **Crossing** and **Tip Entry** Profile



* Data on file



Ordering Information

Balloon Diameter (mm)	Balloon Working Length (mm)			
	5	8	10	15
0.85	208-053-6J	-	208-103-6J	-
1.0	210-053-6J	210-083-6J	210-103-6J	210-153-6J
1.25	212-053-6J	212-083-6J	212-103-6J	212-153-6J




Compliance Chart

Pressure (atm)	Balloon Diameter (mm)		
	0.85	1.0	1.25
2	0.78	0.94	1.18
4	0.82	0.97	1.22
6 (NOM)	0.85	1.00	1.25
8	0.88	1.03	1.28
10	0.92	1.06	1.32
12	0.95	1.09	1.35
14	0.98	1.12	1.38
16 (RBP)	1.01	1.15	1.42
18	1.05	1.18	1.45
20	1.08	1.21	1.48

Technical Specifications

Proximal Shaft	1.9F
Distal Shaft	2.36F
Catheter Working Length	140 cm
Tip Length	1.5 mm
Marker Band(s)	Single
Guidewire Tracking Lumen	30 cm
Coating	<ul style="list-style-type: none"> • Hyrdophilic (tip to guidewire exit port) • Hydrophobic (guidewire lumen)
Nominal Pressure (NOM)	6atm
Rated Burst Pressure (RBP)	16atm
Balloon Material	Nylon
Balloon Folding	2 pleats
Balloon Diameters (mm)	Ø0.85, 1.0, 1.25
Balloon Lengths (mm)	5, 8, 10, 15

0.85 - 1.25 mm



For more information please visit our website at www.OrbusNeich.com or contact us:

CORPORATE HEADQUARTERS

Unit 303 & 305, 3/F, Building 20E
Hong Kong Science Park
Shatin, N.T., Hong Kong
Phone +852.2802.2288
Fax +852.2507.3532

EMEA HEADQUARTERS

Drs. W. van Royenstraat 5
3871 AN Hoevelaken
The Netherlands
Phone +31.33.254.1150 Toll Free Phone 00800.0254.1150*

* Only for Belgium, Denmark, France, Germany, Ireland, Netherlands, Norway, Sweden and UK

©2020 ORBUSNEICH Medical Corporation or its affiliates. All rights reserved.

Not available for sale in the USA.

#G-70-1060 Rev01

SAPPHIRE and ORBUSNEICH are registered Trademarks of OrbusNeich Medical Corporation.
All data and photos on file. Illustrations are not to be considered as engineering drawings or photos.

OrbusNeich[®]
Pioneers in life-changing technologies